

# XGSPON OLT Stick

## Product Specification

Version: 1.0

This document details the specifications required for optical transceiver modules designed for use in XGSPON applications. With unique 1577nm DML laser and single channel XGSPON OLT MAC, this OLT Stick module brings extra benefits and value to our customers, such as high optical power, low power consumption, low cost, no system management required, zero-touch provisioning and flexible deployment solutions.

**STiCKOPTiCS**

Shenzhen Stick Optics Co., Ltd.

# Contact

Production information .....	1
Features .....	1
Applications .....	1
Absolute Maximum Ratings .....	2
Recommended Operating Conditions .....	2
Electrical Characteristics .....	2
Optical Characteristics .....	3
PIN Definition .....	4
Digital Diagnostic Interface .....	5
Reliability indicators .....	6
Mechanical Specification .....	7

## Production information

### **STK10XGS128OLT**

10G XGSPON STICK SFP+ OLT; 20KM;XGSPON SFP+ OLT;Including a 9.953G 1577nm Tx and a 9.953 1270nm APD-Rx ; I-Temp;



## Features

- Support XGSPON application with a regular switch to replace traditional OLT equipment.
- Integrates an XGS-PON OLT MAC.
- Hot-pluggable SFP+ footprint
- 10G 1577nm DML laser transmitter
- RoHS compliant and Lead Free
- Single 3.3V power supply
- Typical power consumption is 2W, with a maximum of 2.5W.
- Operating temperature range: -40°C to 85°C

## Applications

- XGSPON Access Networks
- FTTX

## Absolute Maximum Ratings

Parameter	Symbol	Min	Typ	Max	Unit	Note
Maximum Voltage Supply	$V_{CC3}$	-	-	3.46	V	-
Storage Temperature	$T_{stg}$	-40	-	+85	°C	-
Relative Humidity	RH	5	-	85	%	-
Receiver Optical Power	OP_RX	-	-	-3	dBm	-

## Recommended Operating Conditions

Parameter	Symbol	Min	Typ	Max	Unit	Note
Power Supply Voltage	$V_{CC3}$	3.14	3.3	3.46	V	-
Power Supply Current	$I_{CC}$	-	-	-	-	-
Operating Temperature (case)	$T_{op}$	-40	-	85	°C	-
Power Consumption	-	-	2	2.5	W	-
Transmission Distance	L	-	-	20	Km	-

## Electrical Characteristics

Parameter	Symbol	Min	Typ	Max	Unit	Note
Supply Voltage	$V_{CC}$	-	3.3	-	V	-
Supply Current	$I_{CC}$	-	-	TBD	mA	-
Input differential impedance	$R_{in}$	-	100	-	$\Omega$	-
differential data input swing	$V_{in-pp}$	100	-	850	mV	TBD
Transmitter Disable Voltage	$V_{dis}$	2	-	-	V	-
Transmitter Enable Voltage	$V_{dis}$	-	-	0.8	V	-
differential data output swing	$V_{out-pp}$	300	-	800	mV	-
SD HIGH	$V_{sd}$	2	-	-	V	-
SD LOW	$V_{sd}$	-	-	0.8	V	-

**Note:**  $T_{op} = -40 \sim 85^{\circ}\text{C}$ ,  $V_{CC} = 3.15 \sim 3.45 \text{ V}$

## Optical Characteristics

Parameter	Symbol	Min	Typ	Max	Unit	Note
<b>Optical Transmitter 10G</b>						
Optical Wavelength	$\lambda$	1575	-	1580	-	-
Spectrum Width	$\sigma$	-	-	1	nm	-
Side mode suppression ratio	SMSR	30	-		dB	-
Optical output power (EOL)	$P_o$	2	-	5	dBm	N1
		4	-	7	dBm	N2
		6	-	9	dBm	E1
Laser off power	$P_{off}$	-	-	-39	dBm	-
Extinction ratio	ER	-	6		dB	-
Transmitter Dispersion Penalty	TDP	-	-	2	dB	-
<b>Optical Receiver 10G</b>						
Upstream data rate	DR	9.952			Gbps	-
Optical Wavelength	$\lambda$	1260	1270	1280	nm	-
Receiver Sensitivity (EOL)	$P_{sens}$	-	-	-26	dBm	N1
		-	-	-28	dBm	N2
		-	-	-30	dBm	E1
Receiver Saturation	$P_{sat}$	-6	-	-	dBm	N1
		-8	-	-	-	N2
		-10	-	-	-	E1
SD Assert	SD_A	-	-	-26.5	dBm	N1
		-	-	-28.5	dBm	N2
		-	-	-30.5	dBm	E1
SD D-assert	SD_D	-40	-	-	dBm	N1
		-40	-	-	dBm	N2
		-40	-	-	dBm	E1
SD Hysteresis	SD_H	0.5	2	6	dB	-
SD Assert Time	-	-	-	24	ns	-

**Note:**  $T_{op} = -40 \sim 85^{\circ}\text{C}$ ,  $V_{CC} = 3.15\sim 3.45\text{ V}$


## PIN Definition

<b>PIN</b>	<b>Symbol</b>	<b>Logic</b>	<b>Power up sequence</b>	<b>Description</b>
1	NC	-	-	-
2	TX_Fail1	LVTTL	OUT	Transmit Laser Fail ;TX_FAULT1 is alternate name, Open-Drain, active High, Pull-up on Host.
3	TX_DIS1	LVTTL	IN	Transmit Disable ; Active High
4	SDA	LVTTL	InOut	2-Wire Serial Interface data line
5	SCL	LVTTL	In	2-Wire Serial Interface Clock
6	MOD_ABS	Ground	-	Module absent indication; Pull-up on host PCB, internally,pulled to GND
7	NC	-	-	-
8	LOS	LVTTL	Out	Low level indicates normal transmission operation
9	NC	LVTTL	IN	
10	GND	-	-	Module Ground
11	GND	-	-	Module Ground
12	RD-	CML	Out	10G/2.5G differential data output; DC coupled
13	RD+	CML	Out	
14	GND	-	-	Module Ground
15	Vcc3_Rx	-	2nd	+3.3V Power Supply for Rx
16	Vcc3_Tx	-	2nd	+3.3V Power Supply for Tx
17	GND	-	-	Module Ground
18	TD+	CML	In	Tx differential input; AC coupled;
19	TD-	CML	In	
20	GND	-	1st	Module Ground

# Digital Diagnostic Interface

**STK10XGS128OLT** is fully compliant with XGSPON OLT module specifications, including 2-wire serial diagnostic memory contents.

SFP+ 2-wire serial diagnostic interface and address map shown as below:



Digital diagnostic range and accuracy defined as below:

Data Addr	Parameter	Range	Accuracy	Notes
96-97	Temperature	-40 to 125°C	±3°C	Case Temp
98-99	V <sub>cc</sub> Voltage	0 to 6.55 V	±3%	-
100-101	10G Tx Bias Current	0 to 262 mA	±3%	Unit value 4uA
102-103	10G Tx Power	-37 to 11.2 dBm	±2dB	Unit value 0.2uW
104-105	10G/1G Rx Power	-40 to 8.2 dBm	±2dB	Unit value 0.1uW


## Reliability indicators

The reliability requirements of XGSPON SFP+ symmetric OLT optical transceiver module are shown in the following table.

<b>Parameter</b>	<b>Description</b>
MTBF	2 million hours, confidence 60%, operating temperature 40°C (Reference GR-468 and SR-332)
Module ESD level requirements	HBM High-speed pins $\pm 1000V$ , Other pins $\pm 2000V$
ESD level requirements for modules mounted on a single board	Installed on the single board to be discharged through $\pm 8KV$ contact, $\pm 15KV$ air discharge.
Module reliability requirements	Accord with Telcordia GR-468-CORE Compatible with Telcordia GR-468-CORE
RE	Meet the Class B limit requirements of GB9254 (or CISPR 22).
CE	Meet the Class B limit requirements of GB9254 (or CISPR 22).
Electrostatic discharge immunity	The test is carried out according to GB/T 17626.2 (or IEC 61000-4-2); Contact discharge $\pm 8kV$ , air discharge $\pm 4kV$ , $\pm 15kV$ , performance criterion B
RF electromagnetic field radiation immunity	The test is carried out according to GB/T 17626.3 (or IEC 61000-4-3); The frequency is 80MHz-6GHz (CE certification EN55032 requires 80MHz-6GHz), the amplitude is 10 V/m, and the performance criterion is A

# Mechanical Specification

**STK10XGS128OLT** XGSPON Stick OLT module is hot pluggable, and fully complies with SFP MAS and SFF-8432 specifications.




## About Stick Optics

Shenzhen Stick Optics specializes in high-speed PON Stick communication technology, offering professional PON Stick solutions. Built on a strong foundation in optical components and backed by robust R&D capabilities, the company delivers a full range of PON Stick products. As an emerging high-tech enterprise, Stick integrates chip-level R&D, manufacturing, and sales under one roof. Its products are defined by high speed, high reliability, and low power consumption.

The company's latest flagship offerings-XGS/XGPON OLT Stick, XGSPON ONU Stick, and XGS Combo Stick-have already captured the attention of multiple industry leaders with their exceptional performance.

**STiCKOPTiCS**

 [sales@ponstickhub.com](mailto:sales@ponstickhub.com), [info@ponstickhub.com](mailto:info@ponstickhub.com)

 [www.ponstickhub.com](http://www.ponstickhub.com)